

Jarfalla CVP 700 Cheque Validation Printer

Jarfalla CVP 700, Cheque Validation Printer is a specialized banking device able to combine cheque handling with printing of receipts and similar forms used at the teller workstation. CVP 700 reads CMC-7 and E13B coded cheques and can at the same time print verification on the backside of the cheque. Silent and high quality inkjet printing method gives a large flexibility regarding fonts and graphic printing. An optional garage for print head refill-ing is available.

The design of CVP 700 is made to fulfil maximal user friendliness and ergonomics. The cheque or slip is dropped in the machine from above and automatically moved horizontally for reading and printing. This feature allows printing in a specific position of the document. This is an advantage when pre-printed documents are used. As an option receipts can be printed on tape as well, using a mounted paper roll.

A double-sided cheque scanner can be integrated in CVP 700. This makes the device a complete teller station for cheque scanning and reading and the ideal terminal for automated and computerized cheque clearing.



Technical specification

Print method

75 nozzles ink jet

Printing height

127.5 mm (½ ")

Print resolution

150 (Vertically) 300 (Horizontally) dpi

Print characteristics

32 characters at 12 cpi (Printing a receipt)
42 characters at 15.5 cpi (Printing a receipt)
42 characters at 12 cpi (Printing validation)
56 characters at 15.5 cpi (Printing validation)

Printing speed

57 mm/sec in receipt printing
38 mm/sec in validation printing

Character set

95 alphanumeric, 35 international
128 x 10 graphic

Bar Code

UPC-A, UPC-E, JAN 8 (EAN8), JAN 13 (EAN13), CODE 39, CODE 128, CODEBAR

Interface

Standard: RS232
Option:
Second RS232
Bi-directional parallel
USB

Consumables

Disposable printhead
Garage for refillable ink tank

Paper roll

Diameter 85 mm
Width 76 mm
Printing width 68 mm

MCR reader

CMC-7, E13B

Scanner

CIS technology
Resolution 203 dpi
Black and white with 16 level greyscale
Height 105 mm
Speed >0.25 m sec

Power

24 V DC, powered by a separate AC/DC converter

Overall printer dimensions

180 x 172 x 135 mm (W x D x H)

Drivers

Windows 95-98, 98SE, ME, 2000, NT 4.x, JFXS
WOSA



Refill tank

JARFALLA INTERNATIONAL AB

Kartvägen 7, SE-175 46; Järfälla, Sweden
Tel. +46 8 580 388 45 Fax. +46 8 580 263 26 E-mail: info@jiab.com, Homepage:www.jiab.com